







Materials Guide

MATERIAL	LEVEL OF MAINTENANCE	STRUCTURAL WARRANTY	FINISH WARRANTY	CARE AND MAINTENANCE	RECOMMENDED DISINFECTION
 Thermory®	Low	10-year limited	None Naturally weathers to a pleasing silver-gray if left untreated.	Clean with mild soap and water. Let dry thoroughly. To maintain original color, regularly apply standard deck oil, such as Cutek® Extreme Wood Protection Oil.	2:1 mix of water and vinegar/add some dish soap. Use brush to scrub surfaces. Rinse and let dry. Wipe down with 3% hydrogen peroxide which will foam and disinfect.
 Recycled Plastic	None	20-year limited structural warranty that also covers splitting, fungal decay and insect damage.		Clean with mild soap and water.	Wipe with disinfecting wipes or 70% isopropyl Alcohol.
 Fusion Advantage™	Low	7-year warranty against rusting, peeling, chipping, cracking, mold, mildew, fading and defects in materials and/or workmanship.		Clean with mild soap and water.	Wipe with disinfecting wipes or 70% isopropyl Alcohol. Please Note: Chlorine Bleach may cause surface discoloration.
 Powder Coat	Low	3-year warranty against rusting, peeling, chipping, cracking, mold, mildew and defects in materials and/or workmanship. 7-year warranty against fading		Clean with mild soap and water.	Wipe with disinfecting wipes or 70% isopropyl Alcohol. Please Note: Chlorine Bleach may cause surface discoloration.
 Stainless Steel, Anodized Aluminum and Galvanized Steel	Low	20-year limited	None on Stainless Steel or Aluminum 7-year on galvanized steel	Use a high-quality, non-abrasive cleaner that is specially formulated for stainless steel or aluminum. Clean galvanized steel with mild soap and water.	Wipe with 70% isopropyl alcohol. 3%-6% Hydrogen Peroxide may also be used on stainless steel. Please Note: Chlorine Bleach will cause corrosion and surface discoloration.
 Natural Stone and Roto-Molded Plastic	Low	5-year limited	None	Clean with mild soap and water.	Spray with 3%-6% Hydrogen Peroxide. Please Note: Peroxide is recommended for natural stone because of the foaming action.

